

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
19 August 2004 (19.08.2004)

PCT

(10) International Publication Number
WO 2004/069415 A1

(51) International Patent Classification⁷: B02C 2/04

NILSSON, Mattias [SE/SE]; Kärby Gård, S-275 94
Sjöbo (SE).

(21) International Application Number:
PCT/SE2004/000152

(74) Agent: CARLSSON, Lars-Åke; Sandvik AB, Intellectual Property, S-811 81 Sandviken (SE).

(22) International Filing Date: 6 February 2004 (06.02.2004)

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: Swedish

(26) **Publication Language:** English

(30) Priority Data:
0300328-2 10 February 2003 (10.02.2003) SE

(71) Applicant (for all designated States except US): SANDVIK AB [SE/SE]; S-811 81 Sandviken (SE).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

(72) Inventors; and

(75) Inventors/Applicants (for US only): NILSSON, Kent [SE/SE]; Köpenhamnsvägen 41C, S-217 71 Malmö (SE).

[Continued on next page]

(54) Title: METHOD AND CONTROL SYSTEM FOR STARTING CRUSHING INA GYRATORY CRUSHER



(57) Abstract: In a method for starting crushing in a gyratory crusher, the following steps are carried out: a) that a driving device (10) is started and brings a crushing head (3) to execute a gyratory pendulum movement and that a first width of a gap (6) is set, b) that a supply of material in the gap (6) is commenced, c) that the resulting load on the crusher is measured, d) that the width of the gap (6) is adjusted so that the load approaches a desired value, e) that a measure which is representative of the width of the gap (6) after adjustment is read, and f) that the read measure which is representative of the width of the gap (6) after adjustment is utilized for calculation of a gap width for use as first width of the gap (6) in carrying out step a) upon a next-coming starting-up of a crushing course. By means of the method, the mechanical load on the crusher is decreased and the efficiency is increased.

WO 2004/069415 A1